


# RXCommander User Manual

Version 1.1 (10 nov. 11)



- 1) Main VFO display, indicate actual frequency on the receiver :
  - a) Left mouse click to select VFO operating mode.
  - b) Left mouse click on the figures to change frequency directly
  - c) Right mouse click to locate the displayed frequency on the Station list or the nearest.
  
- 2) Rotary tuning dial :
  - a) Left mouse click on the left/right side of the dial to change frequency at speed = 1
  - b) Right mouse click to change frequency at speed = 2
  - c) Shift + Left mouse to change frequency at speed = 3
  - d) Alt + Left mouse to change frequency at speed = 4
  
- 3) Frequency & Channel direct input keyboard :
  - a) To set 900.000 KHz press : 9 0 0 ENT
  - b) To set 14100.000 KHz press : 1 4 . 1 MHz
  - c) If in channel operation, select channel 1 -199 and press ENT
  - d) Press CLR to reset false input sequence
  
- 4) Receiver & software functions :
  - a) VFO = VFO mode
  - b) Channel = channel mode
  - c) Locked = select Lock/Unlock receiver mode. Unlock = rx buttons and functions enabled.
  - d) Mute = Audio output is muted
  - e) RX ON/OFF = Switch OFF (stand-by) the receiver. Only JRC-535 !
  
- 5) Receiver controls
  - a) NB is only available on the JRC-535 and select only NB ON/OFF , NB1 or NB2
  - b) Not all functions may be available on all models ( eg. ECSS optional board, etc)
  
- 6) Current radio status
  
- 7) Selected Channel Indicator
  - a) Left click to select Channel operating mode.
  
- 8) S-Meter indication ( JRC-535 only )
  
- 9) Channels buttons CH + / CH –
  - a) Left click change channel +/- by 1 channel
  - b) Right click change channel +/- by 10 channels
  
- 10) Frequency buttons Freq + / Freq –
  - a) Change frequency by selected value (see 11)
  - b) Keep pressed by automatically repeat function.

11) Frequency buttons change step value

- a) 10Hz to 12,5KHz
- b) Step USER can be freely setup in the rxcommander.ini files. Default 25000 = 25KHz

12) Main Station database list

- a) Double click to select a specified station and send data to the receiver
- b) Click on the columns title bars to sort the list ( ascending or descending value).
- c) Right click to select functions menu
  - i) Store actual radio status to a specified channel
  - ii) Copy selected Station to a specified channel

13) General program options and functions

- a) New = add a new Station entry copying from current radio status
- b) Delete = remove permanently a Station from the list
- c) Edit = modify data of the current selected Station
- d) Add/Remove filter = Stations display criteria
- e) To Timer = copy current selected Station to the Timer list for timer operations mode
- f) To Log = store current radio status to the LOG list
- g) To Prefs = copy current selected Station to the Preferred list. (short preferred stations list)
- h) SVR ON/OFF = connect – disconnect to the RXC-Server

14) PBS : Pass Band Filter remote control, right click to reset center position. ( only JRC-535)

15) BWC : Bandwidht remote control (JRC-535 only and with ECSS option board installed).